

Frequency Range (MHz)	33-50	150-174	450-470
Intermodulation Rejection per EIA-603, part 4.1.9	≥-67	≥-70	≥-62
Adjacent Channel Selectivity per EIA-603, part 4.1.6	≥-64	≥-80	≥-55
Spurious Response & Image Rejection (dBm) per EIA-603, part 4.1.8	≥-80	≥-80	≥-75
Frequency spread allowable without re-tuning (MHz)	+/-4.9	+/-1.5	+/-10.6

REFERENCE SENSITIVITY*
(12dB SINAD): < 0.35 microvolts

HUM AND NOISE*

Squelched: > -57 dB

Unsquelched: > -37 dB

AC WALL TRANSFORMER (UL LISTED)

Input: 108 to 128 VAC, 60 Hz

Output: 9VDC @ 500 mA

Operating Environment: -30 to +60C

Operating Current: <100mA. standby
<400mA. Max.

STANDARD SIGNALING FORMATS

Number of codes: Up to 6 Activation Codes,
programmable

Two-Tone Sequential or Single Tone:

300 Hz-3000 Hz, tolerance +/- 1.5%

DTMF: 1-12 digits

Two-Tone and DTMF Decode Sensitivity:

<20 dB Sinad

OPTIONAL SIGNALING FORMATS

Federal Signal (MSK) Digital Option:

1200,N,8,1 Synchronous, 1200 Hz mark tone,
1800Hz space tone

Digital Decode Sensitivity: <12 dB Sinad

EAS/SAME Option:

User Programmable to any EAS Event codes
and up

to three (3) location codes

EAS/SAME Decode Sensitivity: <18 dB Sinad

CTCSS/CDCSS:

Decode with Two-Tone codes > 400 Hz only.

Tone Frequency Range 36.6 to 254.1 Hz,

Tone Accuracy > .05Hz

Tone Decode Bandwidth +/- 1.1%

CTCSS/CDCSS (Continued):

Digital, Golay (23,12) 23 bit digital word

Digital Data Rate 134.4 Hz nominal

Decode: Turn on Time < 250ms., Turn off Time <
1.2s.

Acoustic Output: 85 dBA**

RECHARGEABLE BATTERY

Type: Sealed Lead Acid

Rating: 6 VDC, 1.2 A/H

Minimum life without AC power:

6 Hours @ 25% run time, full volume

DRSO600 Option

Dual Relay Output (optional):

5a @ 30 VDC

600 Ohm Output (optional):

50mv - 2.5vpp into 600 Ohms

Antenna: Removable rubber duck

External Antenna Connector: 50 ohm, BNC
female

Model IS2 Strobe (optional): 100 Candela,
60 flash min.

DIMENSIONS

Height x Width x Depth: 5" x 7" x 2-1/2" (10,
incline)

Weight: 4 lbs

ORDER INFORMATION

G1A1FSI2999A Low Band, 33-50 MHz

G3A1FSI2999A VHF High Band, 151-174 MHz

G4A1FSI2999A UHF Band, 450-470 MHz

G1A1FSR2999A Low Band with Relay

G3A1FSR2999A VHF with Relay

G4A1FSR2999A UHF with Relay

Options

I-EAS Installed EAS

I-EAS-KIT Field Installable EAS Kit

I-FSK Installed FSK

I-FSK-KIT Field Installable FSK Kit

I-SW Programming Software

Compatible with Windows 95, 98, 2000, and XP

Dual Relay/600 ohm output models are also available.

Add **IO** to the model number when ordering. The Dual

There is a programming fee associated with Informers

programmed at the factory. Contact your local

representative for a quotation.

The Informer is designed for wall mounting. Mounting
screws are not included.

*Receiver Specifications referenced to TIA/EIA 603

**Acoustic Output measured at 10' on axis in an anechoic
environment. User configurable soft-tones (approximately,
55d BA)